


Twisted assembling cable - 2 x 1 mm² - 17 AWG

Highlights:

- Twisted & separable wires
- Different colors for pair identification
- · Reduced crosstalk due to twisting

Product information:

The PR460x series are twisted assembling cables with a section of 2 x 1.0 mm². They come in various versions with a total of nine different colour combinations, allowing a clear overview when running different cables through each other. The conductors are composed of thin and dense strands oxygen free copper and jacketed by flexible PVC. Both conductors are twisted with a fine pitch which reduces the crosstalk between adjacent cables. This makes the PR46xx series cables perfectly suited for integrated cabling purposes such as 19" equipment racks, internal assembly of loudspeaker units or many other wiring purposes where multiple channels are combined.



Properties:



PROCAB - PR460X - 25/04/2024 13:57 UTC

Inner Conductors:




Product Features:

Application	AV & IT
Series	Bulk & Accessories

Physical Characteristics:

Inner conductor	Material		BC 56 x 0.15 mm (Ø) (OFC)
	Section		1 mm²
	Insulation	Material	PVC 2.6 mm (Ø)
		Colours	Black / Yellow (PR4604)
	Number of conductors		2
	American Wire Gauge		17 AWG
	Insulation	Colours	Black / Brown (PR4605)
			Black / Red (PR4602)
			Black / Orange (PR4603)
			Black / Green (PR4605)
			Black / Blue (PR4606)
			Black / Purple (PR4607)
			Black / Grey (PR4608)
Type of cable			2-core loudspeaker cable
Inner conductor	Conductor twisting		Yes

Cross sections:



Variants:

- PR4602/1 100 meter, black & red
- PR4604/1 100 meter, black & yellow
- PR4605/1 100 meter, black & green
- PR4607/1 100 meter, black & purple
- PR4608/1 100 meter, black & grey
- PR4609/1 100 meter, black & white
- PR4601/1 100 meter, black & brown