

### Highlights:

- 13 AWG thin and dense stranded conductors
- Parallel & separable wires
- Color coded polarity identification

### Product information:

The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible PVC jacket. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.



### Inner Conductors:



### Product Features:

|             |                    |
|-------------|--------------------|
| Application | AV & IT            |
| Series      | Bulk & Accessories |

### Physical Characteristics:

|                 |                          |                               |
|-----------------|--------------------------|-------------------------------|
| Type of cable   | 2-core loudspeaker cable |                               |
| Inner conductor | Material                 | BC 30 x 7 x 0.12 mm (Ø) (OFC) |
|                 | Section                  | 2.5 mm <sup>2</sup>           |
|                 | Number of conductors     | 2                             |
|                 | American Wire Gauge      | 13 AWG                        |
| Outer jacket    | Material                 | Flexible PVC 4 x 8 mm (Ø)     |
|                 | Colours                  | Black with red molded line    |

## Mechanical Characteristics:

---

Temperature range Fixed installation - 40 °C till + 80 °C

Mobile installation - 25 °C till + 70 °C

Bending radius Fixed installation 8 x outer diameter

Mobile installation 10 x outer diameter

## Electrical Characteristics:

---


Capacitance Cond/Cond 118 pF / m @ 1 kHz

Lead resistance 0.9 Ω / 100 m

Cable Crosstalk Min. 74 dB / 100 m

## Cross sections:

---



## Variants:

---

- RZ25/1 - 100 meter